



- UNDERGROUND SERVICE
3-#10 WIRES IN CONDUIT
- PANEL BO. 00-20 - 100 AMP.
- 1 - 30 AMP - 230V. " COOKING TOP
 - 1 - 30 AMP - 230V. " OVEN
 - 1 - 20 AMP - 230V. " DRYER
 - 1 - 20 AMP - 115V. " REFRIGERATOR
 - 1 - 20 AMP - 115V. " WASHER (CLOTHS)
 - 1 - 20 AMP - 115V. " DISH WASHER
 - 1 - 20 AMP - 115V. " ICEBOX
 - 1 - 20 AMP - 115V. " TELEVISION
 - 1 - 20 AMP - 115V. " GENERAL PURPOSE
- PANEL BO. 00-12 - 100 AMP.
- 1 - 40 AMP - 230V. " AIR CONDITIONER
 - 20 AMP - 115V " GENERAL PURPOSE
- PANEL BOARD & SWITCH NUMBERS LISTED ARE SQUARE D.

MATERIAL AND FINISH SCHEDULE						
SPACE	FLOOR	WALLS	CEILING	BASE	WAINSCOT	REMARKS
LIVING	CONC.	AS NOTED	WD. PANELING	WOOD		
DINING	CONC.	AS NOTED	WD. PANEL.	WOOD		
FAMILY	CONC.	AS NOTED	WD. PANEL.	WOOD		
BEDROOMS	CONC.	AS NOTED	PLASTER	WOOD		
BATHS	TELEBOARD	PAINT	PLASTER	TILE	4" x 6", 6" x 6" x 1/2", 6" x 6" IN SPONGE	
KITCHEN	CONC.	WD. PANEL.	WD. PANEL.	WOOD		
ENTRY	CONC.	AS NOTED	WD. PANEL.	WOOD		
CLOSETS	CONC.	AS NOTED	WOOD	WOOD		
TERRACE	CONC.	AS NOTED	WD. PANEL.	WOOD		
STORAGE	CONC.	NONE	NONE	NONE		

WALLS NOTED WITH "WALL COVERING" SHALL BE COVERED WITH FABRICATION - SEE SPECS. (BY OTHERS)
INTERIOR WALLS NOTED "WOOD PANELING" SHALL BE T&G-V-JT LIPRESS OR LARCH (PREFERRED)
"WALL COVERING" TO BE MOUNTED OVER 1/2" PLYWOOD.

DOOR SCHEDULE						
MARK	WIDTH	HEIGHT	THICKNESS	CODE	TYPE	REMARKS
(1)	2'-8"	7'-0"	1 3/4"	SOLID	FLUSH	
(2)	2'-8"	6'-8"	1 3/8"	HOLLOW	FLUSH	
(3)	2'-8"	6'-8"	1 3/8"	HOLLOW	FLUSH	
(4)	2'-8"	7'-8"	1 3/8"		VANI-FLEX	BY MFR.
(5)	2'-8"	6'-8"	1 3/8"		LOUVE	
(6)	11'-8" (EYES)	7'-0"	1 3/8"		LOUVE	GRANT-131-12'
(7)	2'-8"	7'-0"	1 3/8"		LOUVE	
(8)	2'-8"	6'-8"	1 3/8"		SCREEN	
(9)	11'-8" B.A.	7'-6 1/2"			SLID. GLASS	BY MFR. 2 PANELED
(10)	6'-8" B.A.	7'-6 1/2"			SLID. GLASS	" " 2 PANELED

Note: No Screens Req'd. for Slid. Glass Doors.

WINDOW SCHEDULE					
MARK	WIDTH	HEIGHT	TYPE OF GLASS	TYPE	REMARKS
(1)	2'-0 1/2"	7'-0 3/4"	1/2" COP. LIT. CLEAR	JALOUSIE	
(2)	2'-4 1/2"	"	"	"	
(3)	2'-0 1/2"	"	"	"	
(4)	2'-1 1/2"	"	"	"	
(5)	11'-0 1/2" (EYES)	3'-10 1/2"	"	"	
(6)	2'-9 1/2"	7'-2 3/4"	"	"	

GENERAL NOTES

- ALL EXTERIOR WOOD PANELED WALLS SHALL HAVE 3" BATTEN TYPE INSULATION STAPLED BETWEEN STUDS. CEILING AREA ABOVE BEDROOMS SHALL HAVE 3" BATTEN INSULATION BETWEEN CEILING JOISTS. CEILING AREA ABOVE LIVING, DINING, ENTRY, KITCHEN & FAMILY AREAS SHALL HAVE 3" BATTEN TYPE INSULATION STAPLED BETWEEN JOISTS. AREA WALLS SURROUNDING A.C. SPACE SHALL RECEIVE 3" BATTEN INSULATION.
- PLUMBING NOTES: SUPPLY FOR RESIDENCE SHALL BE 1" PLAGE NOT MORE THAN 2 FEET ON 1/2" LINE. ALL PIPING UNDER SLAB SHALL BE GALVANIZED WROUGHT IRON. ALL OTHER PIPING SHALL BE GALV. STEEL. ALL WASTE AND VENT LINES SHALL BE VICTORY HT. CAST IRON. STUB IN FOR FUTURE W.C. & LAV. IN STORAGE RM. (COMPLETE WITH VENT). CARRY HOT & COLD WATER LINES TO UTILITY SPACE FOR WASHER. PROVIDE DRAIN & VENT AS REQ'D. (SEE SPECS. FOR HOOK-UP OF UTILITIES SUPPLIED BY OWNER). STUB OUT GAS CONNECTIONS FOR FUTURE HEATER AT FIRE PLACE, FOR H.W.H. & FOR AIR CONDITIONING UNIT IN LOCATIONS SHOWN. CARRY GAS SUPPLY PIPE TO A POINT 5'-0" FROM EAST SIDE OF BLDG. FOR CONNECTION TO AN UNDERGROUND TANK.

PLUMBING FIXTURES					
FIXTURE	LOCATION	MAKE	CAT. NO.	COLOR	FITTINGS
LAVATORY	BATH #2	AMER. STAND.	F-141-11	WHITE	
TUB	BATH #2	"	D-224E-11	"	
W.C.	BATH #2	"	F-2005-1	"	
SHOWER	BATH #1	"	E-100	"	
SINK	KITCHEN	"	D-7015-1	WHITE	NO REARER REQUIRED
H.W.H.	GEN. SFD.	BRIDGEMAN	BRIDGEMAN MODEL (SOGGLOW)		

DRIVE BY OWNER.